▲Stop 11 Rpad 8,000 S OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION __ 20 __TOWNSHIP Wilcoxen PARTY CHIEF: _ CREW: -TYPE OF MARKER: Harrison METHOD OF ESTABLISHMENT: ____County: 4-25-00 IN. S.P.C. E ZONE NAD '83 14042001 488782.9258(m) NAME: N: E: 61048.4623(m) Section Line 2300 1. 7. 4.40_ Stop 11 8000 S 116.43 96.12 6. 2. (PWP) 4. 3.

Original post set 1820 by Hendricks with witness: 30" beech N 31 W 10 links, 12" dogwood S 67 E 28 links per Marian County Atlas pg. 9. Hosbrook 6-10-1851 called no stone, but witness: SE corner of school house N 4 W 30 1/2 links, per Perry Township Legal Survey Book pg. 24. Cleveland 12-10-72 called railroad spike 4" down. McLand 4-25-73 called the same. Wilcoxen 9-26-78 called same. Excavated by Wilcoxen 7-26-95 and PK nail fd at surface. No railroad spike fd. No stone fd. Corner set per contruction ties. Harrison set. Re-tied 4-25-00 by Wilcoxen. Re-tied 4-27-05 by Wilcoxen.

REF.	DISTANCE	DESCRIPTION
1.	105.49	Most westerly corner of stone column : Movie Gallery
2.	116.43	PK nail SW light pole no # 24"up
3.	106.94	NF corner of brick/block
4.	132.55	NW corner of brick/block
5,	126.70	PK noil F PwP#302-789 30"up
6,	96.12'	PK nail N PwP#170-789 18"up
7.	440'+/+	Due W to C/L of Madison Avenue
8.	137.76'	PK nail S PwP#634-789 12"up